
MEGAVISION®
PROFESSIONAL VIDEO SURVEILLANCE

MV-8595-S4-C-VF

8MP Dual Illumination Water-proof Turret Network Camera





FEATURES

- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution:8MP (3840 × 2160)
- Auto day/night switch
- 3D DNR, HWDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- 30~40m white light view distance; 30~50m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support P2P function
- Support SMD
- Dual-system backup
- Support line crossing detection, region intrusion detection, abandoned/missing object detection, video exception detection
- Support remote monitoring by smart phones& tablet PCs with iOS and Android

MEGAVISION®
PROFESSIONAL VIDEO SURVEILLANCE

SPECIFICATIONS

Model	MV-8595-S4-C-VF
Camera	
Image Sensor	1 / 2.8 "CMOS
Image Size	3840×2160
Electronic Shutter	1 / 3 s - 1 / 100000 s
Iris Type	DC Iris
Min.Illumination	0.02 lux@F1.6,AGC ON; 0 lux with illumination on
Lens	2.8~12mm@F1.6
Field of view	Horizontal: 97.3°~34°; Vertical: 52.3°~17.7°; Diagonal: 116°~37°
Focus	Motorized
Lens Mount	Φ14
Day & Night	ICR
WDR	120dB
BLC	Yes
HLC	Yes
Digital NR	Yes
S/N Ratio	≥50dB
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264
	Sub /Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	8MP(3840×2160),6MP(3200×1800), 4MP(2688×1520), 2K(2560×1440), 1080P
	(1920×1080), 720P (1280×720), D1, VGA (640×480), 640× 360, 480× 240, CIF
Main stream	60Hz: 8MP(1~20fps) /6MP/4MP/2K/1080P (1~30fps)
	50Hz: 8MP(1~20fps) /6MP/4MP/2K/1080P (1~25fps)
Sub stream	720P/D1/VGA/640×360/CIF/480× 240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Third stream	720P/D1/640×360/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
Bitrate	64 Kbps ~ 12 Mbps
Bitrate Type	VBR / CBR
Audio Compression	G711A / U
ROI	Each ROI to be configured separately
Image setting	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image
	Mirror, Image Flip, NR, etc. adjustable through client software or web browser
Interfaces	
Network	RJ 45
Audio	1CH audio input; 1 CH built-in MIC
Video Output	No
Reset	Yes
Storage	Built-in micro SD card slot; up to 256GB

*All pictures and specifications are for reference only and are subject to change without prior notice

SPECIFICATIONS


Functions	
Remote Monitoring	Web browser / MV NVR/NVMS2.X/Mobile APP
Web browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 10 users;
	Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS,
	SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, P2P, QoS
Interface Protocol	ONVIF
Smart Alarm	Motion detection, SMD, SD card full, SD card error, IP address conflict, cable disconnection,
	video exception (scene change, video blur and abnormal color detection)
General Function	Watermark, IP address filtering, video mask, heartbeat, smart supplement light,
	corridor pattern, image distortion correction, ANR, cloud upgrade
Security	Video encryption, firmware encryption, configuration encryption, illegal login lock, IP address filtering,
	802.1x authentication, basic and digest authentication for HTTP/RTSP
Storage	Network remote storage; micro SD card storage
POE	Yes, IEEE802.3af
Ingress Protection	IP67
Supplement Light Range	IR range: 30 ~ 50 m; white light range: 30 ~ 40 m
Smart Event	Line crossing /region intrusion detection(human/motor vehicle/non-motor
	vehicle classification), abandoned/missing object detection


DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8-12mm(W)	88m(288ft)	35m(114ft)	17m(56ft)	8m(27ft)
2.8-12mm(T)	277m(908ft)	111m(364ft)	55m(180ft)	28m(91ft)

Others	
Power Supply	DC12V/PoE
Power Consumption	<12W
Storage Conditions	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 130.7 × 110.2
Weight (net)	Approx. 0.66 kg
Installation	Wall mounting, ceiling mounting,
Certificate	CE, FCC
Enviromental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and
	REACH(EC1907/2006)

*All pictures and specifications are for reference only and are subject to change without prior notice

DIAGRAM





*All pictures and specifications are for reference only and are subject to change without prior notice