

G4 Doorbell Pro

UVC-G4 Doorbell Pro

Datasheet	In The Box	Marketing Images	Accessories	Installation Guide
-----------	------------	------------------	-------------	--------------------

^ Overview

Dimensions	160.6 x 51.7 x 28.7 mm (6.3 x 2 x 1.1")
IR Night Vision	6 m (20 ft)
Smart Detections (People, Vehicles, Animals)	✓
Resolution	FHD
Field of View	Main camera: H: 138°, V: 114°, D: 155° Package camera: H: 97.5°, V: 79.4°, D: 118.2°
Audio	Two-way audio
Weatherproofing	IPX4
Mounting	Flat wall, 20° wedge (Included)
NFC Card & Keyfob Access	✓
Two-Way Intercom & Doorbell Access	✓

^ Performance

Networking Interface	802.11a/b/g/n/ac WiFi Bluetooth 5.0 GbE support (With UACC-Adapter-DBPOE)
Video	
Max. Frame Rate	30 FPS
Resolution	Main camera: 2MP 1600 x 1200 (4:3) Package camera: 2MP 1600 x 1200 (4:3)
Optics	

Sensor	Main camera: 5MP CMOS Package camera: 8MP CMOS
Lens	Fixed focal length
Night Mode	Built-in IR LED illumination and IR cut filter
^ Hardware	
Max. Power Consumption	10W
Power Method	16–24V AC, 1.25A Max., 50/60 Hz USB-C power cable, 5V DC, 2A
Processor	Quad-core Arm® Cortex®-A53 based chip
Weight	Device: 253 g (8.9 oz) With flat wall mount: 286 g (10.1 oz) With 20° wedge mount: 325 g (11.5 oz)
Enclosure Material	Polycarbonate, aluminum alloy
Mount Material	Flat wall mount: aluminum alloy 20° wedge mount: polycarbonate
Button	(1) Ring button (1) Factory reset
Compatible Chimes	Mechanical Broan-NuTone: LA126WH, LA11WH, LA39WH Heath Zenith: SL-2735 Craftmade: CTPW-RG Newhouse Hardware: CHM3D
	Digital Broan-NuTone: LA600WH IQ AMERICA: DW-2850, DW-2840
Ambient Operating Temperature	-10 to 40° C (14 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC
Transformer Specifications ⓘ	
Included in the box for EU version	✓
Input Rating (5, 6)	230V, 50/60Hz
Input Rating (1, 4)	16V AC, 15VA
Ambient Operating Temperature	-5 to 35° C (23 to 95° F)

