

G5 Bullet

UVC-G5-Bullet

Datasheet

In The Box

Marketing Images

Accessories

Installation Guide

^ Overview

Dimensions

Without mount: $\varnothing 75.5 \times 74.4$ mm
($\varnothing 3 \times 2.9$ ")

With mount: $\varnothing 75.5 \times 150$ mm
($\varnothing 3 \times 5.9$ ")

IR Night Vision

9 m (30 ft)

Smart Detections (People, Vehicles, Animals)

✓

Resolution

2K

Field of View

H: 84.4°, V: 45.4°, D: 99.8°

Audio

Microphone

Weatherproofing

IP55

Tamper Resistance

IK04

Mounting

Wall, ceiling, pole mount (Included)
Junction box (Optional)

^ Performance

Networking Interface	10/100 MbE RJ45 port
Video	
Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay
Max. Frame Rate	30 FPS
Resolution	4MP 2688 x 1512 (16:9)
Optics	
Sensor	5MP CMOS
Lens	Fixed focal length
Night Mode	Built-in IR LED illumination and IR cut filter
^ Hardware	
Max. Power Consumption	4W
Supported Voltage Range	37—57V DC
Power Method	PoE
Processor	Dual-core Arm® Cortex®-A7 based chip
Pole Mount Diameter	3/4" (19 mm)
Weight	Without mount: 225 g (8 oz) With mount: 315 g (11.1 oz)
Enclosure Material	Polycarbonate, aluminum alloy
Mount Material	Wall mount: aluminum alloy, polycarbonate Pole mount: aluminum alloy
Button	(1) Factory reset
Ambient Operating Temperature	-20 to 40° C (-4 to 104° F)
Ambient Operating Humidity	0 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC